

HP ANTI RUST

RUST CONVERTER SOLUTION, PROTECTS METAL AGAINST RUST

PURPOSES

HP Anti Rust is used for processing new metal products before painting and for protection to products, which are already damaged by corrosion processes. The product stops corrosion chemically, transforms rust into strong protective superficial layer and stops the rust from spreading.

HP Anti Rust is recommended to use for cars, boats, gardening inventory and other products. HP Anti Rust is not for application on surfaces previously covered with drying oil, paint varnish or other film-forming or water-repellent materials.

MAIN ADVANTAGES

- ✓ Advanced formula, improved ecological characteristics
- ✓ Combines chemically with metal, has high adhesion ability
- ✓ Is highly effective against corrosion damages
- ✓ Forms a firm, strong, protective superficial layer on a metal, which increases wear resistance and stability against aggressive environments
- ✓ The covering is fire-resistant up to 1500°C
- ✓ No colour or smell
- ✓ Fire and explosion proof
- ✓ Stops already started corrosion processes, prevents the occurrence of rust

DIRECTIONS FOR USE

Before applying HP Anti Rust, always clean the surface of all dirt, dust or other contaminants. HP Anti Rust may be applied with a brush, roller, spray gun or by immersing at the temperature above +5⁰C (with humidity under 75%). Apply 1–2 coats with an interval of 40–60 minutes with normalized total consumption not lower than 100–130 g/m².

You can paint or cover the surface with other decorative materials after 24–48 hours. Climate conditions like low temperatures and/or high relative humidity can lengthen the drying time.

Do not mix HP Anti Rust with other products! Stir thoroughly before applying! (Bottom sediment doesn't affect the quality of the product)

SAFETY MEASURES

Keep locked up and out of the reach of children. Wear suitable protective clothing, gloves and eye/face protection. In case of contact with eyes or mouth, rinse immediately. If you feel unwell seek medical advice. Use only in well-ventilated areas. Discard with other household waste products.

COMPOSITION

Ferric(III)hydrophosphate, orthophosphoric acid, water and additives.

STORAGE AND TRANSPORTATION

Store and transport HP Anti Rust in hermetically sealed original containers separately from food products. Keep at temperature above -5°C. The storing period of the product is 24 months.

Xi Irritating to eyes and skin