

## HOLZ OIL

### *DECORATIVE AND PROTECTIVE PRODUCT FOR SURFACE TREATMENT OF WOOD, STONE AND CONCRETE*

#### **Purposes**

Holz Oil protects and cares for wood, stone and concrete surfaces it is suitable for both internal and external conditions. It could be used for processing new and previously oiled wood for residential and domestic buildings (facades, wooden terraces, garden and outdoor furniture, windows, doors etc.).

Holz Oil forms a thin film on the surface that protects, smoothes and makes the surface more beautiful and also provides protection from water and weather conditions.

#### **Directions for use**

Before applying Holz Oil, always clean the surface of all dust, dirt or other contaminants. Holz Oil may be applied with a brush, roller, sprayer or immersing at the temperature above +5<sup>0</sup> C (with humidity under 80 %). Stir thoroughly before applying! (Bottom sediment doesn't affect the quality of the product).

If necessary it can be diluted with white spirit. Oil tinting is possible by adding a pigment.

Apply 2–3 coats with an interval of 40 minutes with normalized total consumption being 60 –80 g/m<sup>2</sup> (1 l on 12–16 m<sup>2</sup>, for planed wood - consumption being 10-15 m<sup>2</sup>/l, for sawn wood - 5-8 m<sup>2</sup>/l).

The extra oil can be remove by sponge or clean textile.

Before processing untreated wood with oil, pre-treat the surface with wood protection (Holz Bio, Grunt Natur etc.)..

The dried and treated surface can be painted or covered with other decorative materials. After completing the work, tools and equipment should be cleaned with soap and water or white spirit.

#### **Safety measures**

Keep locked up and out of the reach of children. In case of contact with eyes or mouth, rinse immediately. If you feel unwell seek medical advice.

Holz Oil is a flammable liquid. It is necessary to comply with fire safety. Oil-contaminated rags collect and place in a fire-resistant container. Use only in well-ventilated areas.

Do not pour into drains and waterways.

#### **Composition**

Various oils, including natural drying oil, odorless solvent and additives.

#### **Storage and transportation**

Store and transport Holz Oil in hermetically sealed original containers away from food products. Keep the temperature above -5° C. The storing period of the product is 36 months.



Edukas Eesti Ettevõtte 2014  
Krediidireiting AA