

HP RENOVATOR

The effective solution for quick wood renovation

Purposes

HP Renovator is used for quick renovation of wood, it cleans of dirt and darkness. It is designed for cleaning the facades, wooden houses, terraces, deck etc. It cleans well freshly sawn wood from darkness. It is possible to treat such types of timber as teak and mahogany.

The product is suitable for both internal and external application. The application on concrete and mineral bases is possible.

Main advantages

It is the liquid solution with a high penetration, cleans and lightens dirty surfaces. It restores the natural colour of timber. **HP Renovator** is chlorine- and chlorine compounds free and therefore does not destroy the wood. It is possible to re-apply the product. After the treatment the strength and durability of wood increase. The treated surface can be painted or over-coated with other protective materials

HP Renovator does not contain biocides. The solution is water based, odourless, non-toxic, fire- and explosion safe material.

Directions for use

HP Renovator is applied on surfaces cleaned of dirt, dust and other coverings with brush, roller or spray at the temperature not lower than +5°C, providing the normalized total consumption not lower than 100-150 ml/m². Let it work for 10-20 minutes. Scrub treated surface with brush whilst rinsing with water or use a pressure washer (max 80 bar). In case of heavily soiled surface procedure could be repeated. Avoid the liquid absorption on the surface, which can damage the colored surface. If the liquid to get to the colored surface, wash immediately with plenty of water.

The dried processed surface can be covered with oil (for example, Holz Oil and others) and other protective and decorative materials.

Do not mix it with other solutions. Shuffle before application, sediment is possible but it doesn't affect on the quality of product.

Safety measures

Keep locked up and out of the reach of children. When using **HP Renovator**, wear suitable protective clothing, gloves and eye/face protection. In case of contact with eyes or mouth, rinse with plenty of water immediately. If you feel unwell seek medical advice. Use in well ventilated areas. Discard with other household waste products.

Composition – Ferric (III) dihydrophosphate, oxalic acid, additives and water.

Storage and transportation

Store and transport **HP Renovator** in hermetically sealed original containers separately from food products. Keep at temperature above -5°C. The storing period of the product is 24 months.

Please read the user manual carefully before using.

